



RH-KBC

BLINDNIETMUTTERN GESCHLOSSEN, MIKROKOPF, RÄNDELSCHAFT, STAHL CHROM 6 FREI VERZINKT

Gewinde	Bezeichnung	Blechdicke Min - Max T [mm]	A Ref	Empfohlenes Loch + 0.1 /-0 [mm]	D [mm]	B [mm]	K [mm]	L [mm]
M4 x 0.7	RH-KBC-0420	0.5-2.0	11.0	6.0	5.9	7.0	0.5	15.0
M4 x 0.7	RH-KBC-0435	2.0-3.5	11.0	6.0	5.9	7.0	0.5	16.5
M5 x 0.8	RH-KBC-0520	0.5-2.0	12.5	7.0	6.9	8.0	0.5	16.5
M5 x 0.8	RH-KBC-0535	2.0-3.5	12.5	7.0	6.9	8.0	0.5	18.0
M6 x 1.0	RH-KBC-0630	0.5-3.0	15.5	9.0	8.9	10.0	0.6	20.5
M6 x 1.0	RH-KBC-0645	3.0-4.5	15.5	9.0	8.9	10.0	0.6	22.0
M8 x 1.25	RH-KBC-0830	0.5-3.0	17.0	11.0	10.9	12.0	0.65	23.0
M8 x 1.25	RH-KBC-0845	3.0-4.5	17.0	11.0	10.9	12.0	0.65	24.5
M10 x 1.5	RH-KBC-1030	1.0-3.0	18.2	13.0	12.9	14.0	0.7	24.5
M10 x 1.5	RH-KBC-1050	3.0-5.0	18.2	13.0	12.9	14.0	0.7	26.0