



FH-KBC

BLINDNIETMUTTERN GESCHLOSSEN, FLACHKOPF, RÄNDELSCHAFT, STAHL CHROM 6 FREI VERZINKT

| Gewinde | Bezeichnung | Blechdicke Min - Max T [mm] | A Ref | Empfohlenes Loch + 0.1 /-0 [mm] | D [mm] | B [mm] | K [mm] | L [mm] |
|-----------|-------------|-----------------------------------|----------|---------------------------------------|-----------|-----------|-----------|-----------|
| M4 x 0.7 | FH-KBC-0420 | 0.5-2.0 | 11.3 | 6.0 | 5.9 | 9.0 | 0.8 | 16.0 |
| M4 x 0.7 | FH-KBC-0440 | 2.0-4.0 | 11.3 | 6.0 | 5.9 | 9.0 | 0.8 | 18.0 |
| M5 x 0.8 | FH-KBC-0530 | 0.5-3.0 | 11.5 | 7.0 | 6.9 | 10.0 | 1.0 | 17.0 |
| M5 x 0.8 | FH-KBC-0550 | 3.0-5.0 | 11.5 | 7.0 | 6.9 | 10.0 | 1.0 | 19.0 |
| M6 x 1.0 | FH-KBC-0630 | 0.5-3.0 | 12.7 | 9.0 | 8.9 | 12.3 | 1.3 | 19.2 |
| M6 x 1.0 | FH-KBC-0650 | 3.0-5.0 | 12.7 | 9.0 | 8.9 | 12.3 | 1.3 | 21.0 |
| M8 x 1.25 | FH-KBC-0830 | 0.5-3.0 | 14.8 | 11.0 | 10.9 | 15.0 | 1.5 | 21.5 |
| M8 x 1.25 | FH-KBC-0855 | 3.0-5.5 | 14.8 | 11.0 | 10.9 | 15.0 | 1.5 | 24.0 |
| M10 x 1.5 | FH-KBC-1040 | 1.0-4.0 | 19.2 | 13.0 | 12.9 | 17.0 | 1.6 | 27.0 |